

ICS IE ToughCat 7 S/FTP

Installation cable for tougher environments



Application

Generic Data transmission. This cable is a Cat7 S/FTP cable meant for use as installation (horizontal) cable in tougher electrical and mechanical environment, including ships and offshore units.

Construction

Conductor	: Stranded copper wire Ø 0.27 mm ²
Insulation	: PE, Ø 1.6 mm
Twisting	: 2 Cores to the pair
Lay up	: 4 Pairs
Pair screen	: Al-laminated plastic foil around each pair
Overall screen	: Copper braid, tinned Ø 6,6 mm
Sheath	: Oil resistant, Fire retardant and halogen free LSHF-FR (SHF1)
Marking text	: E.g. "meter" "year" manufacturer ToughCat C7 LSHF-FR 4x2/0.27mm ²

Outer Sheath Colours

Available colours : Grey and Black

Installation recommendations

Min. Bending Radius during Installation	: 8xD
Min. Bending Radius Fix Installed	: 4xD
Max. Conductor Operating Temperature	: 85°C

Standards applied

IEC 61156-5	Transmission characteristics
EN 50173-1	Generic cabling systems
EN 50288-4-1	Multi-Element Metallic Cables
ISO/IEC 11801	Information technology
IEC 60332-3-24	Flame Retardant
IEC 60754-2	Halogen Free
IEC 61034	Low Smoke
IEC 60811-2-1	Chemical resistance

T : +31 (0)168 468 100

E : sales@incore-cables.com

I : www.incore-cables.com

ICS IE ToughCat 7 S/FTP

Range and Dimensions

Article Code	Nominal diameter outer sheath, mm	MJ/km	kWh/m	Weight of Cable Approx. (Kg/Km)
P83B04P0.27BAZGR1	8.1	670	0,186	75

Electrical properties at 20°C

DC loop resistance		< 138 Ω/km
Resistance unbalance		< 2%
Insulation resistance	500 V	> 5000 MΩxkm
Capacitance	at 800 Hz	Nom. 43 nF/km
Capacitance unbalance	pair to ground	< 1500 pF/km
Mean Characteristic impedance	at 100 MHz	100 ± 5 Ω
Nominal velocity of propagation		0,76c
Propagation delay		< 450 ns/100 m
Delay skew		< 15 ns/100 m
Transfer impedance	At 1 MHz At 10 MHz At 30 MHz	< 10 mΩ/m < 8 mΩ/m < 10 mΩ/m
Coupling attenuation	3	> 85 dB

Nominal Transmission characteristics at 20°C

F (MHz)	Attenuation (dB/100m)	NEXT (dB)	ACR (dB/100m)	Return loss (dB)	PS-NEXT (dB)	PS-ACR (dB/100m)	ELFEXT (dB/100m)	PS-ELFEXT (dB/100m)
1	2,0	90	88	-	87	85	85	82
4	3,6	90	86	27	87	83	85	82
10	5,5	90	84	30	87	81	79	76
16	7,5	90	82	30	87	79	75	72
20	7,7	90	82	30	87	79	73	70
31.25	9,8	90	80	30	87	77	69	66
62.50	14,0	86	72	30	83	69	63	60
100	17,9	83	65	30	80	62	59	56
155.00	22,4	81	59	26	78	55	57	54
200.00	25,6	78	52	25	75	49	53	50
250.00	28,8	77	48	25	74	45	51	48
300.00	31,6	73	41	23	70	38	47	44
600.00	45,7	71	25	20	68	22	44	41

NOTICE

Incore Cables has endeavored to ensure the accuracy of the data in this publication, however we cannot be liable for the consequences of errors or omissions. All data is subject to change without notice. The installer and/or user assumes all liability for the consequences of the installation and/or use of any of our products in contravention of any applicable law, regulation or code.

T : +31 (0)168 468 100

E : sales@incore-cables.com

I : www.incore-cables.com

